

TULIP

Distributed by

Teagle

MULTIDISC

200-900 (XL) (H)



MULTIDISC 200-900 H + Accessories

Article number	Description	Transport width mm	Open roller Ø mm	Number of discs	Power required hp	Max. power hp	Weight with OR/PR500 kg
745-200	Multidisc 200	2000	440	14	50	100	690/800
745-250	Multidisc 250	2500	440	18	60	110	880/1010
745-300	Multidisc 300	3000	440	22	70	130	1220/1365
745-400	Multidisc 400	4000	520	30	90	170	1620/1780
746-400	Multidisc 400 H	2980	440	30	100	170	2115/2315
746-450	Multidisc 450 H	2980	440	34	120	200	2320/2555
746-500	Multidisc 500 H	2980	440	38	150	250	2675/2960
746-600	Multidisc 600 H	2980	440	46	180	320	3030/3320
746-800	Multidisc 800 H	2980	440	62	240	400	5320/5705
746-900	Multidisc 900 H	2980	440	70	270	450	5850/6285
747-300	Multidisc 300 XL	3000	520	22	100	150	1430/1620
747-400	Multidisc 400 XL	4000	520	30	130	190	1770/1930
748-400	Multidisc 400 XL H	2980	520	30	130	190	2265/2465
748-450	Multidisc 450 XL H	2980	520	34	155	220	2490/2720
748-500	Multidisc 500 XL H	2980	520	38	185	250	2865/3150
748-600	Multidisc 600 XL H	2980	520	46	220	320	3260/3550
748-800	Multidisc 800 XL H	2980	520	62	250	400	5630/6015
748-900	Multidisc 900 XL H	2980	520	70	290	450	6200/6635

Accessories Multidisc 200-900 (XL) (H): www.tulipindustries.com



Multidisc 400 H with packer roller

The very robust 3-point linkage frame is suitable for category II and III. Up from 4 meter working width Tulip offers you the Multidisc hydraulically foldable version. Each section of the hydraulically foldable models is mechanically locked during transport. A double acting hydraulic cylinder is used to fold the machine.



In transport position the Tulip hydraulic foldable Multidisc is only 3 meter wide. Thanks to the compact construction the machine can be linked very close behind the tractor.

The Multidisc is provided with 2 rows of discs with a relative distance of 80 cm. Through this the soil is well prepared. The Multidisc is available with an open roller or a packer roller.



The discs are made out of special steel and have a diameter of 51 cm. Other diameters are available on demand. The heavy bearings and strong wheel hubs with big lubricator chambers guarantee low maintenance. The torsion bar suspension gives every disc a maximum freedom of movement.



ROTERRA



MULTITERRA



MULTIDISC



MULTIDISC PLUS



MULTIVATOR



ROTARYTILLER



POLYMAT



CENTERLINER



Peeters Agricultural machinery

Munnikenheiweg 47, 4879 NE Etten-Leur (NL)
Tel.: 0031 (0)76-5046666, Fax: 0031 (0)76-5046699
info@tulipindustries.com, www.tulipindustries.com